

DHI-ASR1200E-D

Dahua ID Card Water proof Access Reader



- Made from ABS materials.
- Contactless card reading for ID card.
- Communicates through RS-485 and Wiegand34 protocols.
- Buzzer and indicator light.
- Offers overcurrent and overvoltage protection.
- Protects against lightning and short circuits, and is antistatic.
- Watchdog monitors and controls the device when it behaves abnormally, performing recoveries when necessary to ensure the long- term operation of the device.
- IP66 rated.
- Suitable for use both indoors and outdoors.
- Supports surface mount.

Technical Specification

System	
OSDP Protocol	Yes
Basic	
Product Type	Card reader
Buzzer	Yes
Casing Material	ABS
Function	
Unlock Mode	Supports card swiping
Card Type	ID card
Modulation Type	AM
Frequency Range	125 kHz
Max Transmission Power	66 dBuA/m @10 m
Performance	
Response Time	0.1 sec
Card Reading Distance	0 cm–3 cm (0"–1.18")
Port	
RS-485	1
Wiegand	1
General	
Power Supply	12 VDC, 0.5 A
Protection	IP66 rated
Power Consumption	0.6 W

Product Dimensions	97.0 mm × 44.0 mm × 17.0 mm (3.82" × 1.73" × 0.67")
Packaging Dimensions	122.0 mm × 92.5 mm × 58.0 mm (4.80" × 3.64" × 2.28")
Operating Temperature	–30 °C to +65 °C (–22 °F to +149 °F)
Operating Humidity	5%–95% (RH), non-condensing
Operating Environment	Outdoor
Gross Weight	0.11 kg (0.25 lb)
Installation	Surface Mount
Certifications	CE; FCC

Ordering Information

Type	Model	Description
Access Reader	DHI-ASR1200E-D	Dahua ID Card Water proof Access Reader

Dimensions (mm[inch])

